

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) A method of translating ~~a set of transmission parameters~~ at least one quality of service (QoS) parameter related to a first cell-based transmission protocol from said first cell-based transmission protocol to a second transmission protocol for a data element being sent on a connection from a first cell-based communication network utilizing said first transmission protocol to a second communication network utilizing said second transmission protocol, said method comprising:

mapping ~~a first said at least one QoS parameter from said set of transmission parameters~~ to a class of service value for said connection; and

mapping said class of service value ~~and a second parameter from said set of transmission parameters~~ to another parameter indicating a quality of service provisioning for said second transmission protocol,

wherein said at least one QoS parameter includes at least one of a service category, cell loss ratio and cell delay variation.

2. (Currently Amended) A method of translating ~~a set of transmission parameters~~ at least one QoS parameter as claimed in claim 1, wherein ~~said first parameter is a quality of service parameter for said connection in said first communication network and said second parameter is~~ said at least one QoS parameter further includes a priority rating for said data element.

3. (Currently Amended) A method of translating ~~a set of transmission parameters~~ at least one QoS parameter as claimed in claim 2, further comprising:

converting said data element of said connection from at least one first data element associated with said first transmission protocol to a second data element associated with said second transmission protocol; and

Application No. 10/023,643

- 5 -

associating said ~~value of said~~ another transmission parameter with said second data element.

4. (Currently Amended) A method of translating ~~a set of transmission parameters~~ at least one QoS parameter as claimed in claim 3, wherein said ~~second~~ at least one QoS parameter further indicates drop precedence and said another transmission parameter indicates a quality of service provisioning for said connection in said second communication network and drop precedence for said second data element in said second communication network.
5. (Currently Amended) A method of translating ~~a set of transmission parameters~~ at least one QoS parameter as claimed claim 4, wherein said second communication network is a[[n]] MPLS network, said second transmission protocol is a MPLS transmission protocol and said second data element is a MPLS frame.
6. (Currently Amended) A method of translating ~~a set of transmission parameters~~ at least one QoS parameter as claimed in claim 5, wherein said first communication network is an ATM network, said first transmission protocol is an ATM transmission protocol and each of said at least one first data element is an ATM cell.
7. (Currently Amended) A method of translating ~~a set of transmission parameters~~ at least one QoS parameter as claimed in claim 6, wherein said MPLS frame is provided to said MPLS network for transmission through a label switched path and said ~~value of said~~ another transmission parameter is inserted in an experimental field of said MPLS frame.
8. (Cancelled)
9. (Currently Amended) A method of translating ~~a set of transmission parameters~~ at least one QoS parameter as claimed in claim [[8]] 7, wherein said ~~value of said~~ drop precedence of said at least one ATM cell utilizes a value of drop precedence for said each of said at least one ATM cell.
10. (Currently Amended) A method of translating ~~a set of transmission parameters~~ at least one

123081-339668
TDO-RED #8310962 v. 3 8

QoS parameter as claimed in claim 9, wherein said label switched path is an experimental inferred per hop behaviour label switched path (E-LSP).

11. (Currently Amended) A method of translating ~~a set of transmission parameters~~ at least one QoS parameter as claimed in claim 3, wherein said second communication network is a [[n]] MPLS network, said second transmission protocol is a MPLS transmission protocol, said second data element is a MPLS frame said first communication network is an ATM network, said first transmission protocol is an ATM transmission protocol, each of said at least one first data element is an ATM cell, said second parameter indicates drop precedence for said ATM cell, said another transmission parameter indicates drop precedence for said MPLS frame, said MPLS frame is provided to said MPLS network for transmission through a label inferred per hop behaviour label switched path (L-LSP) and said ~~value of said another transmission~~ parameter is inserted in an experimental field of said MPLS frame.

12. (Currently Amended) A translation module of a network element, said translation module translating ~~a set of transmission parameters~~ at least one quality of service (QoS) parameter related to a first cell-based transmission protocol from said first cell-based transmission protocol to a second transmission protocol for a data element being sent on a connection from a first communication network utilizing said first transmission protocol to a second communication network utilizing said second transmission protocol, said network element connected to said first communication network and said second communication network, said network element receiving said data element from said first communication network and communicating said data element to said translation module, said network element transmitting said data element from said network element over said second communication network after translation of said ~~set of transmission parameters~~ at least one QoS parameter, said translation module comprising:

- a first sub-module mapping ~~a first said at least one QoS parameter from said set of transmission parameters~~ to a class of service value for said connection; and
- a second sub-module mapping said class of service value ~~and a second parameter from said set of transmission parameters~~ to another transmission parameter indicating a quality of service provisioning for said second transmission protocol,

wherein said at least one QoS parameter includes at least one of a service category, cell loss ratio and cell delay variation.

13. (Currently Amended) A translation module of a network element as claimed in claim 12, wherein ~~said first parameter is a quality of service parameter for said connection in said first communication network and said second parameter is~~ said at least one QoS parameter further includes a priority rating for said data element.

14. (Currently Amended) A translation module of a network element as claimed in claim 13, further comprising:

a conversion sub-module, said conversion sub-module:

converting said data element of said connection from at least one first data element associated with said first transmission protocol to a second data element associated with said second transmission protocol; and
associating said ~~value of said~~ another transmission parameter with said second data element.

15. (Currently Amended) A translation module of a network element as claimed in claim 14, wherein ~~said second~~ at least one QoS parameter further indicates drop precedence and said another transmission parameter indicates ~~a quality of service provisioning for said connection in said second communication network and~~ drop precedence for said second data element in said second communication network.

16. (Currently Amended) A translation module of a network element as claimed in claim 15, wherein said second communication network is a $[[n]]$ MPLS network, said second transmission protocol is a MPLS transmission protocol and said second data element is a MPLS frame.

17. (Original) A translation module of a network element as claimed in claim 16, wherein said first communication network is an ATM network, said first transmission protocol is an ATM transmission protocol and each of said at least one first data element is an ATM cell.

Application No. 10/023,643

- 8 -

18. (Original) A translation module of a network element as claimed in claim 17, said translation module further comprising:

a MPLS card, said MPLS card containing said second sub-module and said conversion sub-module of said translation module; and

a control complex connected to said MPLS card, said control complex providing management for said network element, said control complex containing said first sub-module of said translation module;

wherein said network element includes an ATM card, said ATM card providing an interface for said ATM network, said ATM card receiving said at least one ATM cell from said ATM network and communicating said at least one ATM cell to said translation module, said ATM card is a line card, said MPLS card is a line card, said MPLS card providing an interface for said MPLS network and said MPLS card transmitting said MPLS frame over said MPLS network.

19. (Currently Amended) A translation module of a network element as claimed in claim 18, wherein said network element transmits said MPLS frame over said MPLS network through a label switched path and said ~~value of said~~ another transmission parameter is inserted in an experimental field of said MPLS frame.

20. (Cancelled)

21. (Currently Amended) A translation module of a network element as claimed in claim ~~[[20]] 19~~, wherein said ~~value of said~~ drop precedence of said at least one ATM cell utilizes a value of drop precedence for said each of said at least one ATM cell.

22. (Original) A translation module of a network element as claimed in claim 21, wherein said label switched path is an experimental inferred per hop behaviour label switched path (E-LSP).

23. (Currently Amended) A translation module of a network element as claimed in claim 14, wherein said second communication network is a[[n]] MPLS network, said second transmission protocol is a MPLS transmission protocol, said second data element is a MPLS frame said first

Application No. 10/023,643

- 9 -

communication network is an ATM network, said first transmission protocol is an ATM transmission protocol, each of said at least one first data element is an ATM cell, said second parameter indicates drop precedence for said ATM cell, said another transmission parameter indicates drop precedence for said MPLS frame, said MPLS frame is provided to said MPLS network for transmission through a label inferred per hop behaviour label switched path (L-LSP) and said ~~value of said~~ another transmission parameter is inserted in an experimental field of said MPLS frame.

24. (new) A method of formatting a MPLS packet to support a quality of service (QoS) parameter related to an ATM cell when said MPLS packet is transmitted on a MPLS communication network, said method comprising:

mapping said QoS parameter to a class of service value for a MPLS connection for said MPLS packet;

mapping said class of service value to another parameter indicating a quality of service provisioning for said MPLS communication network;

inserting class of service value into a experimental field of a header of said MPLS packet;
and

inserting contents of said ATM cell in said MPLS packet,

wherein said QoS parameter includes at least one of a service category, cell loss ratio and cell delay variation.

25. (new) A method of routing an ATM cell through a MPLS network, said method comprising:

mapping a quality of service (QoS) parameter related to the ATM cell to a class of service value for a MPLS connection for said MPLS network;

mapping said class of service value to another parameter indicating a quality of service provisioning for said MPLS communication network;

creating a MPLS packet;

inserting class of service value into a experimental field of a header of said MPLS packet;

inserting contents of said ATM cell in said MPLS packet;

123081-339668
TDO-RED #8310962 v. 3

Application No. 10/023,643

- 10 -

routing said MPLS packet through one or more router in said MPLS communication network according to contents of said another parameter,

wherein

said QoS parameter includes at least one of a service category, cell loss ratio and cell delay variation; and

said contents of said another parameter specify experimental (EXP) inferred label switched path scheduling treatment and drop precedence treatment.

* * * * *

123081-339668
TDO-RED #8310962 v. 3 8